



**POLYCAB WIRES PVT. LTD.**

PCC LP NO. 3 / 2018-19 Dtd : 1st August 2018

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables , Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm,4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

**Aluminium Armoured**

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XWay / A2XFay	A2XWY / A2XFY	A2XWY / A2XFY	A2XFY	A2XWY / A2XFY
2.5		72	80		92
4		78	86		99
6		91	100		113
10		108	126		141
16	71	124	134		161
25	91	139	181	203	220
35	103	161	215	242	269
50	125	200	272	314	347
70	160	268	366	427	470
95	180	344	454	515	573
120	216	409	543	644	702
150	257	494	670	762	865
185	314	616	819	951	1074
240	385	801	1047	1197	1371
300	469	976	1265	1467	1653
400	589	1229	1608	1868	2100
500	807	1626	2179	2539	2850
630	942	2046	2889	3450	3856
800	1298				
1000	1497				

**EXTRA FOR SPECIAL CONSTRUCTION:**

a) Round Wire Armouring	
- 2 x 16 & above	25%
- 3 x 16 & 3.5CX25 & above	25%
- 4 x 10 & above	25%
- For Single core 95 & above	25%
b) Stranding 10 sq.mm and below	10%
c) Extruded PVC Innersheath Up 50	5%
Extruded PVC Innersheath 70 & Above	2.5%
d) HR PVC Insulation	10%
e) HR PVC Inner Sheath	5%
f) HR PVC Outer Sheath	5%
g) Oxygen Index (FR)	2.5%
h) PVC Insulated Cables	8%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
		Power (Al.)		
Upto 16	10%	7.5%	15%	20%
25 - 50	7.5%	7.5%	12.5%	15%
70 & above	5%	5.0%	15%	12.5%
		Power Single Core (Al.)		
Upto 16	-N.A-	10%	-N.A-	25%
25 - 50	-N.A-	10%	-N.A-	20%
70 & above	-N.A-	7.5%	-N.A-	17.5%

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



**POLYCAB WIRES PVT. LTD.**

PCC LP NO. 3 / 2018-19 Dtd : 1st August 2018

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

**Aluminium Unarmoured**

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XY	A2XY	A2XY	A2XY	A2XY
4		51	55		61
6		57	65		77
10		68	84		99
16	39	81	107		132
25	55	114	156	178	190
35	64	135	187	213	237
50	84	174	245	283	311
70	111	233	339	390	433
95	151	313	419	485	543
120	189	374	518	609	677
150	229	454	642	735	840
185	282	568	798	925	1043
240	353	754	1021	1178	1337
300	433	931	1255	1448	1635
400	569	1193	1576	1826	2062
500	677	1500	2054	2374	2678
630	807	1891	2721	3219	3613
800	1131				
1000	1330				

**EXTRA FOR SPECIAL CONSTRUCTION:**

a) Stranding 10 sq.mm and below	10%
b) Extruded PVC Innersheath Up 50	5%
Extruded PVC Innersheath 70 & Above	2.5%
c) HR PVC Insulation	10%
d) HR PVC Inner Sheath	5%
e) HR PVC Outer Sheath	5%
f) Oxygen Index (FR)	2.5%
g) PVC Insulated Cables	8%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath Unarmd.	Inner Sheath	Outer Sheath
<b>Power (Al.)</b>				
Upto 16	10%	7.5%	15%	20%
25 - 50	7.5%	7.5%	12.5%	15%
70 & above	5%	5%	15%	12.5%
<b>Power Single Core (Al.)</b>				
Upto 16	-N.A-	10%	-N.A-	25%
25 - 50	-N.A-	10%	-N.A-	20%
70 & above	-N.A-	7.5%	-N.A-	17.5%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



# POLYCAB WIRES PVT. LTD.

PCC LP NO. 3 / 2018-19 Dtd : 1st August 2018

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

## Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY	2XWY / 2XFY
4		137	178	225	296	355	415
6		183	244	314	411	480	572
10		291	392	505	746		
16	203	415	554	728	1001		

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XWY/2XFY		Number of Cores	2XWY/2XFY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	81	105	14	333	462
3	99	133	16	344	521
4	118	165	19	399	610
5	138	198	24	499	765
6	158	230	27	557	852
7	175	260	30	638	982
8	198	292	37	778	1199
10	254	342	44	945	1483
12	292	400	61	1290	2021

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM )	4%
C) Extruded Innersheath	2.50%
D) Round Wire Armouring	
1C x 95 sq. mm & above	7.50%
1.5 sq.mm - 12 core & above	15%
2.5 sq.mm - 9 core & above	15%
10 sq.mm - 4 core & above	15%
16 sq.mm - 2 core & above	15%
16 sq.mm - 3 core & above	15%
E) OXYGEN INDEX (FR)	2.50%
F) HR PVC Insulatoin	7%
HR I/S & O/S	5% Each
G) FRLS Loading-Power Cable (upto 6 Sq.mm.)	7.50%
FRLS Loading-Power Cable (10 Sq.mm. & above)	4%
H) PVC Insulated Cables	5%

Cores	FRLS Loading Factor- Control Cable		LSZH	
	Inner Sheath	Outer Sheath Armoured	Inner Sheath	Outer Sheath
2 to 4 Core	5%	6%	15%	15%
5 to 10 Core	5%	4%	15%	15%
12 & Above	5%	4%	12.50%	12.50%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



# POLYCAB WIRES PVT. LTD.

PCC LP NO. 3 / 2018-19 Dtd : 1st August 2018

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

## Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core
	2XY	2XY	2XY	2XY
4		111	156	201
6		157	222	290
10		259	366	480
16	188	370	541	715

### Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XY		Number of Cores	2XY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	57	81	14	270	419
3	71	104	16	306	480
4	89	133	19	360	567
5	106	159	24	455	713
6	125	190	27	509	798
7	142	218	30	583	914
8	165	249	37	712	1121
10	198	307	44	844	1347
12	234	364	61	1161	1852

### EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM )	4%
C) Extruded Innersheath	2.5%
D OXYGEN INDEX (FR)	2.5%
E) HR PVC Insulation	7%
HR PVC I/S & O/S	5% Each
F) FRLS Loading-Power Cable (upto 6 Sq.mm.)	7.50%
FRLS Loading-Power Cable (10 Sq.mm. & above)	4%
G) PVC Insulated Cables	5%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
Unarmd				
2 - 4	5%	6%	15%	15%
5 - 10	5%	4%	15%	15%
12 & Above	5%	4%	12.5%	12.5%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



**POLYCAB WIRES PVT. LTD.**

PCC LP NO. 3 / 2018-19 Dtd : 1st August 2018

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

**Copper Armoured**

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY
25	336	634	908	1093	1196	1633
35	455	866	1249	1434	1649	2255
50	615	1176	1703	1991	2256	3086
70	866	1664	2419	2818	3232	
95	1217	2389	3473	4058	4649	
120	1530	2997	4365	5199	5851	
150	1903	3737	5448	6283	7303	
185	2342	4598	6704	7838	8981	
240	3006	5914	8637	10067	11576	
300	3748	7365	10753	12541	14424	
400	4911	9656	14110	16316	18925	
500	6196					
630	7798					
800	9881					
1000	12334					

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

**Copper Unarmoured**

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	
	2XY	2XY	2XY	2XY	2XY	
25	290	568	851	1027	1125	
35	400	787	1177	1355	1559	
50	547	1076	1615	1889	2139	
70	778	1530	2306	2688	3085	
95	1045	2129	3203	3739	4289	
120	1320	2679	4030	4800	5412	
150	1649	3343	5039	5810	6764	
185	2030	4121	6210	7262	8332	
240	2616	5314	8014	9343	10755	
300	3259	6629	9992	11654	13415	
400	4286	8703	13121	15183	17625	
500	5412					
630	6817					
800	8651					
1000	10810					

**EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):**

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	2.50%
D) Round Wire Armouring	
1C x 95 sq. mm & above	7.50%
10 sq.mm - 4 core & above	15%
16 sq.mm - 2 core & above	15%
16 sq.mm - 3 core & above	15%
E) OXYGEN INDEX (FR)	2.50%
F) HR PVC Insulatoin	7%
HR I/S & O/S	5% Each
G) FRLS Loading-Power Cable (10 Sq.mm. & above)	4%
H) PVC Insulated Cables	5%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



# POLYCAB WIRES PVT. LTD.

PCC LP NO. 3 / 2018-19 Dtd : 1st August 2018

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

## 3 Core HT Cables

Size in Sq.mm.	(Rate in Rs. Per Mtr.)						
	3.3 KV (E) / 3.3 KV (UE)	6.6 KV (E)	6.6 KV (UE) / 11 KV (E)	11 KV (UE)	22 KV (E)	33 KV (E)	33 KV (UE)
35			560				
50			633				
70	659	704	752				
95	798	838	890	1151	1198	1597	
120	939	979	1026	1338	1367	1822	
150	1060	1104	1147	1479	1508	1929	2291
185	1249	1274	1335	1653	1690	2130	2537
240	1480	1541	1601	1945	1981	2437	2877
300	1748	1838	1862	2236	2272	2737	3208
400	2125	2298	2341	2629	2676	3169	3690
<b>EXTRA FOR SPECIAL CONSTRUCTION:</b>							
1) Extruded PVC Inner Sheath		3%					
2) Pressure Extruded PVC Innersheath		13%					
3) Round Wire Armouring - Up to 11 KV (E)		25%					
11 KV (UE) & Above		27.5%					
4) FRLS PVC Inner Sheath		5%					
5) FRLS PVC Outer Sheath		5%					
6) FR Sheath with Oxygen Index		3%					

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



# POLYCAB WIRES PVT. LTD.

PCC LP NO. 3 / 2018-19 Dtd : 1st August 2018

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi conducting compound in combination with Copper tape, AL flat strip / round armoured and overall PVC sheathed cable confirming to IS 7098 / (PART-II) 1985 with latest amendments.

## 1 Core HT Cables

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	3.3 KV (E) / 3.3 KV (UE)		6.6 KV (E)		6.6 KV (UE) / 11 KV (E)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
25						
35					231	243
50					254	268
70	267	281	274	288	292	306
95	303	318	306	323	325	341
120	341	359	344	363	366	386
150	380	401	385	406	402	425
185	437	461	449	472	482	509
240	541	569	552	580	607	638
300	627	660	643	678	708	747
400	750	790	781	822	848	891
500	945	996	991	1044	1027	1080
630	1172	1233	1192	1255	1223	1288
800	1453	1529	1466	1542	1486	1564
1000	1752	1844	1759	1851	1932	2036

### EXTRA FOR SPECIAL CONSTRUCTION:

1) FRLS PVC Inner Sheath	7.5%				
2) FRLS PVC Outer Sheath	5%				
3) Oxygen Index	3%				

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

**POLYCAB WIRES PVT. LTD.**

PCC LP NO. 3 / 2018-19 Dtd : 1st August 2018

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi conducting compound in combination with Copper tape, AL flat strip / round armoured and overall PVC sheathed cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

**1 Core HT Cables**

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	11 KV (UE)		22 KV (E)		33 KV (E)		33 KV (UE)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
25								
35								
50								
70								
95	422	446	438	462	586	616		
120	489	513	494	520	644	679		
150	529	556	538	565	673	708	798	839
185	614	646	630	662	748	787	874	920
240	706	743	724	761	846	890	1037	1092
300	796	837	813	857	991	1044	1143	1203
400	942	991	964	1013	1133	1192	1308	1376
500	1178	1238	1178	1238	1391	1465	1509	1589
630	1398	1469	1398	1469	1630	1716	1767	1859
800	1631	1717	1631	1717	1867	1965	2124	2234
1000	2124	2234	2124	2234	2277	2389	2438	2567

**EXTRA FOR SPECIAL CONSTRUCTION:**

1) FRLS PVC Inner Sheath	5%							
2) FRLS PVC Outer Sheath	5%							
3) Oxygen Index	3%							

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.